(19) World Intellectual Property Organization

International Bureau



1 (1881) 1 (1881) 1 (1881) 1 (1881) 1 (1881) 1 (1881) 1 (1881) 1 (1881) 1 (1881) 1 (1881) 1 (1881) 1 (1881) 1

(43) International Publication Date 29 December 2004 (29.12.2004)

PCT

(10) International Publication Number WO 2004/113160 A1

(51) International Patent Classification?: B63H 9/06, 9/08

(21) International Application Number:

PCT/GB2004/002481

(22) International Filing Date: 9 June 2004 (09.06.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:

GB 0314441.7 20 June 2003 (20.06.2003) 0320544.0 2 September 2003 (02.09.2003) GB

(71) Applicant and

(72) Inventor: TOSTEVIN, Richard, Edmund [GB/GB]; La Balise, La Viltole, Torteval, Guernsey GY8 0PR (GB).

(74) Agent: STANLEY, David, William; Stanleys, Kings Court, 12 King Street, Leeds LS1 2HL (GB).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM,

AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: SAILING BOATS



(57) Abstract: A mast (1) is in the form of an egg-shaped closed loop that extends abeam of a hull (7). A main spar (2) is supported on the mast (1) and extends upwardly from a lower, fore position on the bowsprit (4) to a higher, aft position above the stern (12). A lateen sail (3) of triangular form has its longer side attached to the main spar (2) with its shorter sides depending from the main spar (2). The free corner of the sail (3) is tethered by ropes or sheets (14) to points on the sides of the hull (7) or deck such that it is positioned substantially above the centre line of the hull (7). The sail (3) can be fully deployed within the closed loop shape of the mast (1) without fouling the mast (1). This allows the sail (3) full and unrestricted deployment, results in exceptionally good sailing and provides swift and easy tacking.

